

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1-6. (Canceled)

7. (Previously Presented) A purge system for a fuel cell stack, comprising:

a purge valve to regulate flow from the fuel cell stack;

an actuator coupled to open and close the purge valve;

a purge cell voltage sensor coupled across at least one fuel cell forming a purge cell portion of the fuel cell stack to determine the voltage across the purge cell portion;

a fuel cell voltage sensor coupled across at least two fuel cells in the fuel cell stack to determine the voltage across the fuel cells; and

a controller coupled to provide control signals to the actuator to open the purge valve when an average voltage across the purge cell portion of the fuel cell stack falls below a defined first percentage of a threshold voltage measured across the at least two fuel cells wherein the controller is further coupled to provide control signals to the actuator to close the purge valve after a determined purge duration has elapsed, the determination of purge duration being based on a flow of current through the fuel cell stack wherein the controller is further coupled to provide control signals to the actuator to close the purge valve when the average purge cell voltage rises above a defined second percentage of the average fuel cell voltage and wherein the defined second percentage is different than the defined first percentage.

8. (Previously Presented) A purge system for a fuel cell stack, comprising:

a purge valve to regulate flow from the fuel cell stack;

an actuator coupled to open and close the purge valve;

a purge cell voltage sensor coupled across at least one fuel cell forming a purge cell portion of the fuel cell stack to determine the voltage across the purge cell portion;

a fuel cell voltage sensor coupled across at least two fuel cells in the fuel cell stack to determine the voltage across the fuel cells; and

a controller coupled to provide control signals to the actuator to open the purge valve when an average voltage across the purge cell portion of the fuel cell stack falls below a defined first percentage of a threshold voltage measured across the at least two fuel cells wherein the controller is further coupled to provide control signals to the actuator to close the purge valve after a determined purge duration has elapsed, the determination of purge duration being based on a flow of current through the fuel cell stack wherein the controller is further coupled to provide control signals to the actuator to close the purge valve when the average purge cell voltage rises above a defined second percentage of the average fuel cell voltage and wherein the defined second percentage is greater than the first percentage.

9-10. (Canceled)

11. (Original) A fuel cell system, comprising:

a fuel cell stack having a plurality of fuel cells;

a purge valve to regulate a purge discharge from the fuel cell stack;

an actuator coupled to open and close the purge valve; and

a controller coupled to control the actuator to open and close the purge valve in a pulsed purge sequence when a fuel cell stack purge condition exists, the pulsed purge sequence comprising:

opening the valve for a purge duration;

closing the purge valve after the purge duration for a hold period;

repeating the opening and closing of the valve at least once; and then

keeping the valve closed for an inter-purge duration before any subsequent purge.

12. (Original) The fuel cell system of claim 11 wherein the controller is configured to determine if a stack purge condition exists by determining if an average purge cell voltage across a purge cell portion of a fuel cell stack exceeds a percentage of an average fuel cell voltage across at least a portion of the fuel cell stack.

13. (Original) The fuel cell system of claim 11 wherein the inter-purge duration is longer than each of the at least one purge duration and hold period in the pulsed purge sequence.

14-15. (Canceled)

16. (Original) A method of operating a fuel cell purge system with a pulsed purge sequence, comprising:

determining that a fuel cell stack purge condition exists;

operating a purge valve in a pulsed purge sequence comprising:

opening the valve for a purge duration;

closing the purge valve after the purge duration for a hold period;

repeating the opening and closing of the valve at least once for a second purge duration; and then

keeping the valve closed for an inter-purge duration before any subsequent purge.

17. (Original) The method of claim 16 wherein the inter-purge duration is longer than each of the at least one purge duration and hold period in the pulsed purge sequence.

18. (Original) The method of claim 16 wherein the first purge duration is the same as the second purge duration.

19. (Original) The method of claim 16 wherein the first purge duration is different than the second purge duration.

20. (Original) The method of claim 16, further comprising:  
determining at least one of the first and the second purge durations based on a fuel  
cell stack current.

21. (Canceled)

22. (Previously Presented) The method of claim 16 wherein  
determining that a fuel cell stack purge condition exists includes:

determining if an average purge cell voltage across a purge cell portion of a fuel  
cell stack exceeds a percentage of an average fuel cell voltage across at least a portion of the fuel  
cell stack.

23-31. (Canceled)

32. (Previously Presented) A method of operating a fuel cell purge  
system, comprising:

monitoring an average purge cell voltage across a purge cell portion of a fuel cell  
stack;

monitoring an average fuel cell voltage across at least a portion of the fuel cell  
stack;

opening a purge valve if the average purge cell voltage falls below a first defined  
percentage of the average fuel cell voltage;

determining a current flow through the fuel cell stack;

determining a purge duration based on the determined current flow; and

closing the purge valve following a most recently determined one of the  
determined purge durations after opening the purge valve, wherein the second defined percentage  
is different than the first defined percentage.

33-37. (Canceled)

38. (Original) A computer-readable media containing instructions to cause a processor to control operation of a fuel cell system, by:

determining that a fuel cell stack purge condition exists;

operating a purge valve in a pulsed purge sequence comprising:

opening the valve for a purge duration;

closing the purge valve after the purge duration for a hold period;

repeating the opening and closing of the valve at least once; and then

keeping the valve closed for an inter-purge duration before any subsequent purge.

39-43. (Canceled)